

RP50RL FLOOR STANDING TYPE

RP150RL



FLOOR STANDING LINE (electric heaters connected)		RP50RL
Cooling output	Frig/h	11178
Cooling output	W	13000
Cooling output	BTU	44330
Heating output	Kcal/h	13672
Heating output	W	15900
Heating output	BTU	54219
Humidity extraction rate	L/h	3,0
Cooling electric power	W	4585
Heating electric power	W	7410
EER		2,84
Energy efficiency class		C
Annual energy consumption	kWh	2292,5
COP		2,15
Power supply	V - Hz	400 – 50
N° of phases		3+N
Max power input cooling	W	6100
Max power input heating	W	8950
Rated cooling current	A	7,55
Rated heating current	A	12,20
Starting current	A	63
Noise level I.U. max	dB(A)	55
Noise level O.U. max	dB(A)	65
I.U. air capacity (max speed)	m³/h	2000
Indoor unit dimensions (WxHxD)	mm	605x1900x350
Outdoor unit dimensions (WxHxD)	mm	980x1250x412
Indoor unit weight	Kg	60
Outdoor unit weight	Kg	117
Type of refrigerant		R410a
Refrigerant charge	Kg	3,40
Suction pipe diameter	in	3/4
Delivery pipe diameter	in	3/8
Max refrigerating pipe length	m	15
Max standard charge pipe length	m	4
Supplementary charge pipe	g/m	50
Maximum difference in level	m	5
Type of scroll compressor		SANYO



RPO50RL



Remote controller